

Drill Hole				Athabasca Group - Basement Unconformity Depth (m)	SRC Geoanalytical Results				Grade (U3O8%) x Thickness (m) (GT)	
Hole ID	Azimuth	Dip	Total Depth (m)		From (m)	To (m)	Interval (m)	U3O8 (wt%)		
AR-14-30	230	-90	807.00	101.10	297.00	389.00	92.00	0.49	45.36	
					including	344.50	361.10	16.60	2.25	110.30
						419.00	464.00	45.00	2.45	
					including	428.00	438.00	10.00	4.96	203.40
					including	452.50	464.00	11.50	4.97	
						466.50	471.00	4.50	15.47	69.62
						488.00	508.00	20.00	10.17	478.92
					including	493.50	508.00	14.50	13.92	
					including	493.50	500.00	6.50	25.22	0.59
						512.50	576.00	63.50	7.54	
					including	520.00	566.00	46.00	10.32	1.45
					including	548.50	555.50	7.00	35.19	
					including	549.00	549.50	0.50	66.80	
						580.00	587.00	7.00	0.08	
						721.00	728.00	7.00	0.21	
Total Composite Grade x Thickness (GT) =									909.63	

- Cutoff grade 0.01% U3O8 (weight %)
- Minimum thickness 0.5m downhole
- Maximum internal dilution 2.00 m downhole
- U3O8 analyzed by ICP-OES at SRC laboratories, Saskatoon
- All depths and intervals are meters downhole

Drill Hole				Athabasca Group - Basement Unconformity Depth (m)	SRC Geoanalytical Results				Grade (U3O8%) x Thickness (m) (GT)	
Hole ID	Azimuth	Dip	Total Depth (m)		From (m)	To (m)	Interval (m)	U3O8 (wt%)		
AR-14-30	230	-90	807.00	101.10	303.00	303.50	0.50	0.07	0.04	
						314.50	317.00	2.50	0.10	0.26
						321.00	323.00	2.00	0.44	0.88
					including	344.50	361.10	16.60	2.25	41.76
						370.00	382.00	12.00	0.15	1.78
						419.50	423.00	3.50	0.24	0.83
						426.00	464.00	38.00	2.88	109.44
					including	428.00	438.00	10.00	4.96	
					including	452.50	464.00	11.50	4.97	69.62
						466.50	471.00	4.50	15.47	
						489.00	508.00	19.00	10.71	203.40
					including	493.50	508.00	14.50	13.92	
						514.00	515.00	1.00	0.76	0.76
					including	517.50	574.00	56.50	8.46	478.05
					including	520.00	566.00	46.00	10.32	
						580.00	585.50	5.50	0.10	0.56
						721.50	728.00	6.50	0.22	1.44
Total Composite Grade x Thickness (GT) =									908.81	

- Cutoff grade 0.05% U3O8 (weight %)
- Minimum thickness 0.5m downhole

- Maximum internal dilution 2.00 m downhole
- U3O8 analyzed by ICP-OES at SRC laboratories, Saskatoon
- All depths and intervals are meters downhole

Drill Hole				Athabasca Group - Basement Unconformity Depth (m)	SRC Geoanalytical Results				Grade (U3O8%) x Thickness (m) (GT)
Hole ID	Azimuth	Dip	Total Depth (m)		From (m)	To (m)	Interval (m)	U3O8 (wt%)	
AR-14-30	230	-90	807.00	101.10	314.50	316.50	2.00	0.11	0.23
					321.50	323.00	1.50	0.56	0.84
					327.50	330.50	3.00	0.26	0.79
					333.50	365.50	32.00	1.28	40.86
				including	344.50	361.10	16.60	2.25	
					371.00	380.00	9.00	0.17	1.55
					420.00	422.50	2.50	0.30	0.76
					427.00	440.50	13.50	3.74	50.45
				including	428.00	438.00	10.00	4.96	
					444.50	464.00	19.50	3.02	58.87
				including	452.50	464.00	11.50	4.97	
					466.50	471.00	4.50	15.47	69.62
					489.00	491.00	2.00	0.77	1.55
					493.50	508.00	14.50	13.92	201.80
				including	493.50	500.00	6.50	25.22	
					514.00	515.00	1.00	0.76	0.76
					517.50	574.00	56.50	8.46	478.05
				including	520.00	566.00	46.00	10.32	
					582.50	585.50	3.00	0.15	0.46
					722.00	728.00	6.00	0.24	1.41
Total Composite Grade x Thickness (GT) =									907.99

- Cutoff grade 0.1% U3O8 (weight %)
- Minimum thickness 0.5m downhole
- Maximum internal dilution 2.00 m downhole
- U3O8 analyzed by ICP-OES at SRC laboratories, Saskatoon
- All depths and intervals are meters downhole

Drill Hole				Athabasca Group - Basement Unconformity Depth (m)	SRC Geoanalytical Results				Grade (U3O8%) x Thickness (m) (GT)
Hole ID	Azimuth	Dip	Total Depth (m)		From (m)	To (m)	Interval (m)	U3O8 (wt%)	
AR-14-30	230	-90	807.00	101.10	321.50	323.00	1.50	0.56	0.84
					327.50	328.00	0.50	0.54	0.27
					330.00	330.50	0.50	0.73	0.37
					338.00	338.50	0.50	0.51	0.26
					344.00	363.00	19.00	2.03	38.532
				including	344.50	361.10	16.60	2.25	
					376.50	377.00	0.50	0.86	0.43
					427.50	438.00	10.50	4.77	50.04
				including	428.00	438.00	10.00	4.96	
					444.50	445.00	0.50	0.51	0.25
					452.00	464.00	12.00	4.80	57.612
				including	452.50	464.00	11.50	4.97	

					466.50	471.00	4.50	15.47	69.62
					489.50	490.00	0.50	2.70	1.35
					493.50	508.00	14.50	13.92	201.80
				including	493.50	500.00	6.50	25.22	
					514.00	515.00	1.00	0.76	0.76
					517.50	566.50	49.00	9.73	476.92
				including	520.00	566.00	46.00	10.32	
					722.00	722.50	0.50	0.63	0.314
					726.50	727.50	1.00	0.55	0.55
Total Composite Grade x Thickness (GT) =									899.91

- Cutoff grade 0.5% U3O8 (weight %)
- Minimum thickness 0.5m downhole
- Maximum internal dilution 2.00 m downhole
- U3O8 analyzed by ICP-OES at SRC laboratories, Saskatoon
- All depths and intervals are meters downhole