

Drill Hole				Athabasca Group - Basement Unconformity Depth (m)	SRC Geoanalytical Results			
Hole ID	Azimuth	Dip	Total Depth (m)		From (m)	To (m)	Interval (m)	U3O8 (wt%)
AR-14-15	320	-70	750.00	130.90	385.30	388.75	3.45	0.04
					406.00	409.30	3.30	0.02
					422.10	427.25	5.15	0.08
					437.20	439.30	2.10	0.05
					498.50	504.95	6.45	0.02
					564.00	586.35	22.35	3.42
				including	576.00	582.85	6.85	10.72
				including	578.10	582.60	4.50	15.74
				including	578.10	580.70	2.60	26.10
				including	579.55	580.00	0.45	55.80
					589.85	590.45	0.60	0.97
					594.00	626.00	32.00	1.52
				including	597.00	612.85	15.85	2.98
				including	606.50	609.65	3.15	10.40
				including	609.30	609.65	0.35	43.70
					672.70	673.70	1.00	0.17
					689.50	695.00	5.50	0.04
Composite parameters:								
· Minimum thickness 0.25m downhole								
· Cutoff grade 0.01% U3O8 (weight %)								
· Maximum internal dilution 2.00 m downhole								
· U3O8 analyzed by ICP-OES at SRC laboratories, Saskatoon								
· All depths and intervals are meters downhole								